



Architectural Concrete Chemicals

223 West Hampton Avenue

Capitol Heights, MD 20743

(301) 336-9300 : (800)638-2672

Fax (301) 336-6597

Tuff Release

PRODUCT DESCRIPTION: Semi-Liquid, high viscosity release which ensures the highest quality architectural and structural surfaces. Will not stain the concrete or affect adhesion of waterproofing or other coatings.

AREA OF APPLICATION: Designed for use with the most intricate molds and forms; Especially with low or no draft applications and when using highly superplasticized (SCC) mixes. May be used on all types of formwork including plastic, rubber or Styrofoam.

DIRECTIONS: Remove any oil or grease residues from the form surface left from previously used releases. Apply Tuff Release in a very thin coat by brush, roller or by spray using a High Volume Low Pressure spray gun or by jiffy mop with on a swivel assembly. Wipe out excess oil with a slightly oil moistened mop or rag. Allow surface to dry prior to concrete placement.

TECHNICAL DATA: Appearance and odor: slight amber in color. Specific gravity is between. Flash point - 145' F. Solubility in water, insoluble.

SHELF LIFE AND STORAGE: Two years from manufacturing date in closed original container.

PACKAGING: 5 gal. Plastic pails, 55 gal. Plastic Drums and 275 gal. totes

SAFETY: Keep away from flames or sparks. Store in cool dry area.

Shipping Classification: **Non-Regulated Material**