



**PRODUCT DATA SHEET**

Edition 12.2018/v1  
CSC Master Format™ 07 27 36  
SPRAYED FOAM AIR BARRIER

# Sika Boom® PRO Cleaner

## CLEANER FOR REMOVING UNCURED PU FOAM FROM SIKA BOOM® PRO DISPENSER

<b>Description</b>	Powerful aerosol cleaner for regular cleaning of the Sika Boom® PRO Dispenser gun.
<b>Where to Use</b>	Sika Boom® PRO Cleaner is used to clean the Sika Boom® PRO Dispenser gun after use. It is for removing fresh uncured polyurethane foam residues from dispensing equipment, but may also be used to remove fresh uncured foam from other surfaces. Sika Boom® PRO Cleaner will also clean and remove grease from contaminated substrates.
<b>Advantages</b>	<ul style="list-style-type: none"> <li>▪ Powerful solvent based easy to use aerosol can.</li> <li>▪ May be used in all positions.</li> <li>▪ May be used on its own or screwed onto the Sika Boom® PRO Dispenser gun.</li> <li>▪ Environmentally Friendly: CFC and HCFC-free.</li> <li>▪ May be used then stored for later use.</li> </ul>
<b>Technical Data</b>	
<b>Packaging</b>	500 mL (460 g) can / 12 cans per case
<b>Colour</b>	Clear
<b>Consumption</b>	Up to 15 Sika Boom® PRO Dispenser gun cleanings
<b>Shelf Life</b>	24 months from the date of production, if it is stored properly in undamaged, original, sealed packaging and if storage conditions are met.
<b>Storage Conditions</b>	Product must be stored in an upright position, in dry conditions, protected from direct sunlight and at temperatures between 18 °C and 20 °C.
<b>Density</b>	0.85 g/ cm <sup>3</sup>
<b>Service Temperature</b>	0 °C to 30 °C
<b>Application Temperature</b>	5 °C to 30 °C
<i>Product properties are typically averages, obtained under laboratory conditions. Reasonable variations can be expected on-site due to local factors, including environment, preparation, application, curing and test methods.</i>	

**HOW TO USE**

**Application**

Before dispensing, shake the can vigorously for 20 seconds to mix contents. Will not remove cured PU foam.

**Cleaning Sika Boom® PRO Dispenser gun:** Mechanically remove any hardened PU residues, then screw the Sika Boom® PRO Cleaner can onto the dispenser gun and hold the trigger for at least 5 seconds allowing the solvent to flush through the gun adaptor, ensuring the dispenser tip is thoroughly cleaned. Repeat if necessary. Sika Boom® PRO Dispenser gun can then be stored attached to the Sika Boom® PRO Cleaner for some time. If stored without being attached to the Sika Boom® Cleaner, we recommend cleaning the dispenser gun thoroughly by repeating the cleaning process several times.

**Cleaning other surfaces:** Attach the spray nozzle that comes with Sika Boom® PRO Cleaner and thoroughly apply to surfaces (including exterior of dispenser gun body) to remove uncured PU foam. Wipe with a clean cloth to remove foam and residual material. Repeat if necessary.

**Limitations**

- Sika Boom® PRO Cleaner can partially dissolve or discolour sensitive substrates (e.g. Varnish, paint, plastics and textiles). We recommend testing the compatibility and colourfastness discretely on an unobtrusive area before every use.
- Cured foam can only be mechanically removed.
- Pressurised container. Protect from sunlight and temperatures over 50 °C. Do not open forcibly or incinerate, even after use. Do not spray towards open flames or onto hot objects. Keep away from ignition sources - no smoking. Keep out of reach of children. May form explosive mixtures without adequate ventilation.

**Health and Safety Information**

For information and advice on the safe handling, storage and disposal of chemical products, users should refer to the most recent SAFETY DATA SHEET containing physical, ecological, toxicological and other safety-related data.

KEEP OUT OF REACH OF CHILDREN

The Information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions, within their shelflife. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any recommendations, or from any other advice offered. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request or may be downloaded from our website at: [www.sika.ca](http://www.sika.ca)

**SIKA CANADA INC.**

**Head Office**

601, avenue Delmar  
Pointe-Claire, Quebec  
H9R 4A9

**Other locations**

Toronto  
Edmonton  
Vancouver

**1-800-933-SIKA**  
**[www.sika.ca](http://www.sika.ca)**

Certified ISO 9001 (CERT-0102780)  
Certified ISO 14001 (CERT-0102791)

