

CP 199



FROGTAPE® PRO GRADE ORANGE PAINTER'S TAPE™



TYPICAL APPLICATIONS

- For interior or exterior use on a variety of surfaces even in hot and humid conditions

PRODUCT FEATURES

- High adhesion
- Conformable backing
- 3-day clean removal without shredding
- Sticks better than beige™
- DOES NOT contain PaintBlock® Technology

CONSTRUCTION

Overall Grade/Function: Production

Backing: Crepe paper

Adhesive: Rubber-based

STANDARD WIDTH(S)

24mm 36mm 48mm

STANDARD LENGTH(S)

55m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength	24 lbs/in width	42.0 N/10 mm
Adhesion to Stainless Steel	39 oz/in width	4.27 N/10 mm
Thickness	6.4 mils	0.16 mm
Elongation	9%	9%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape

TECHNOLOGIES