

# <u>Americas PDS Database</u> > <u>CRC Lithium General Purpose Grease</u>



# **CRC Lithium General Purpose Grease**

# ATTRIBUTES -

#### **Item Number**

1006198

#### **Legacy Number**

73310

#### Case Number

1006197

#### **Product Description**

A high purity, NLGI Grade 2 lithium based grease. Provides superior lubrication & durability in any weather and most temperatures. It is a versatile grease designed for light duty applications requiring a long grease life. Will not break down or run out.

#### **Applications**

Hinges, latches, overhead door tracks, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment. A break-in lubrication for bearings.

# **Unit Package Description**

14 Ounce (414 ml) Cartridge

#### **Brand**

CRC

# **Net Fill** 397 Grams **Unit Dimensions** 23.65H x 5.41W x 5.41D cm

#### **Units Per Case**

10

#### **UPC** Code

78254733104

#### **Case Dimensions**

24.13H x 11.43W x 28.9D cm

# **Appearance**

Amber Semi-Solid to Solid Grease

# Base Type

Lithium-12

# Flash point (F)

482°F

# Flash point (C)

250°C

# Flammability Class - CPSC

None

#### **KB Value**

N/A

# Plastic Safe

Not Determined

# Film Type

Grease

#### Film Thickness

Not Determined

# **Evaporation Rate**

Slow

# **Dielectric Strength**

Not Determined

# Timken Ok Load (lbs)

Not Determined

# **Propellant**

**NSF Number** 

N/A

**DOT Proper Shipping Name** 

Not Regulated

4 Ball EP

Not Determined

4 Ball Wear

< 0.4 mm scar diam.

**Drop Point** 

> 360°F

рΗ

N/A

ISO Viscosity Grade

150

**NLGI** Grade

2

**SAE** Grade

N/A

Water Washout

Not Determined

Working Temp (F)

0 to 250°F

Working Temp (C)

-17.8 to 121°C

Restricted from Sale In:

Not for sale in United States.

Removal (How To)

Remove with a degreaser or brake cleaner product.