



LUBRIKO® **CONCRETE RELEASE 636**

Description

Concrete Release 636 is a ready to use mixture of process oils and naturally derived chemical release agents that prevent bonding of concrete to form.

Features and Benefits

For use on all types of forms; including wood, steel, aluminum, fiberglass and plastic. Can be used daily on equipment and tools to prevent or soften concrete buildup. Concrete Release 636 is a good summer grade product for outdoor forming operations.

Typical Properties

Flash Point		146 °C
Pour Point		-20 °C
Colour (ASTM)		2.0 – 3.0
Viscosity, cSt	@40°C	8.5 – 10.0
Staining		None

Applications

Surfaces should be clean of hardened concrete. On steel forms, remove rust and residues to ensure best results. Applied using low-pressure sprayer, to ensure a light, even coating. When applying via brush, roller, or sponge care should be taken to apply as thinly as possible to guarantee good results. Forms should be re-coated before each use.

Product Features

- Concrete Release 636 does not contain "diesel" or solvents and is extremely user and environmentally friendly.
- Concrete Release 636 is not governed by WHMIS laws.
- Increases life of wooden forms and reduces rust on steel forms when in storage.
- Does not discolor or stain concrete.
- These are cost effective products for a wide range of concrete forming applications

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Commercial Oil Company's knowledge; however, the Commercial Oil Company makes no warranty whatsoever, expressed or implied, and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification

35 BURFORD ROAD, HAMILTON, ONTARIO, CANADA L8E 3C6
905-560-3244 • 1-800-463-1976 • FAX 905-560-2961 • www.commercialoil.ca