



TECHNICAL DATA

HIGH PERFORMANCE LINE STRIPING

PRODUCT #750

PRODUCT DESCRIPTION

Hi-Performance Line Striping #750 is a two-component, 100% solids, rapid cure epoxy coating used for line striping.

ADVANTAGES

- Easy 2 to 1 mix ratio
- Easy to apply using a roller 3/8" high-quality roller cover
- Hi-Build formulation for better hide
- Withstands abrasive wear conditions far longer than safety tape, or spray-on line striping products
- Quick cure for faster project turnaround (typically 3-5 hours at 70 degrees F)

PRODUCT USES

- Aisle striping in factories, warehouses, loading docks, and auto service centers
- OSHA required safety markings
- Vehicular parking stripes in parking garages
- Curbs and steps

LIMITATION

- Do not apply under 45 degrees F
- Do not apply to surfaces that have not been cleaned and abraded
- Do not apply on damp or wet surfaces
- Do not apply less than 20 mils
- Do not leave mixed material in the mixing vessel

PRODUCT APPLICATION

Surface Preparation: The area to be coated must be clean and free of any grease, oils, peeling coatings, or anything else that may interfere with the bond of this product. The area to be coated should be abraded using sandpaper or drywall screen.

Mixing: Combine Part A (resin) with Part B (hardener) using a mixing stick or mixing blade for 2-3 minutes, or until pigment is consistent throughout. This product is a fast-curing epoxy product, after mixing immediately pour material on the floor in ribbons. Materials left in the mixing vessel will become unusable within a few minutes.

Cleanup: Clean skin with soap and water. Tools and equipment should be cleaned with a general-purpose solvent.

Disposal: Properly dispose of in accordance with local and state regulations.

ADVANTAGES

Available in a 1-gallon kit

Colors Available in yellow, red, white, and blue.

COVERAGE (Each kit)

160 linear feet of 6" striping

240 linear feet of 4" striping