

**#4751 SILICA SAND****TYPICAL SCREEN ANALYSIS**

U.S. SIEVE	TYPICAL % RETAINED
30 Mesh	2.5%
40 Mesh	10.00%
50 Mesh	29.00%
70 Mesh	39.00%
100 Mesh	17.50%
140 Mesh	2.00%
AFS	50

**TYPICAL CHEMICAL ANALYSIS**

Silicon Dioxide (SiO <sub>2</sub> )	94.85%
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	0.21%
Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	2.81%
Calcium Oxide (CaO)	0.21%
Magnesium Oxide (MgO)	0.09%
Clay Content	<0.10%
Loss on Ignition (LOI)	<0.50%
Sodium Oxide (Na <sub>2</sub> O)	0.29%
Potassium Oxide (K <sub>2</sub> O)	<0.01%

Colour:	Brown
Grain Shape:	Sub-angular

Sandblast Slags  
Foundry Sands  
Empire Blast Equipment  
Bullard Safety Equipment  
Sandblast Hose & Nozzles  
Walnut Shells & Corn Cob Grit  
Waterjet & Sandblast Garnet  
Schmidt Blast Equipment  
Silica Free Abrasives  
Steel Shot & Grit  
Aluminum Oxide  
Glass Beads

**WARNING:** This product contains free silica. Repeated inhalation of respirable free silica may cause delayed lung injury known as silicosis. Follow current OSHA Safety and Health Standards for Crystalline Silica (Quartz). All products are sold without warranty expressed or implied and seller specifically does not warrant that these products are suitable for a particular purpose or purposes or are merchantable. Buyer agrees it does not rely on seller's skill or judgment to select or furnish these products. Buyer shall make its own tests to determine the suitability of such product for its purposes. 07/19

Tel: (905) 527-6000  
Toll Free Tel: 1-888-794-5665  
Fax: (905) 527-6660  
Toll Free Fax: 1-888-794-7263  
bm-info@allredi-ca.com