# SikaFix® PU Part A



Version Revision Date: SDS Number: 1.2 12/21/2016 100000004232

#### **SECTION 1. IDENTIFICATION**

Product name : SikaFix® PU Part A

Manufacturer or supplier's details

Company name Sika Canada Inc.

601, avenue Delmar

Pointe-Claire, QC H9R 4A9

Canada www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

#### Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

## **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 4

**GHS** label elements

Signal Word : Warning

**Hazard Statements** : H227 Combustible liquid.

**Precautionary Statements** : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

hol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

# SikaFix® PU Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 12/21/2016
 100000004232

#### Other hazards

None known.

## Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

## **Hazardous ingredients**

No hazardous ingredients

#### **SECTION 4. FIRST AID MEASURES**

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician : Treat symptomatically.

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

: Water

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

# SikaFix® PU Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 12/21/2016
 100000004232

for fire-fighters

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Environmental precautions : Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

: Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors or spray mist.

For personal protection see section 8. No special handling advice required.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Protect from frost.

Materials to avoid : No special restrictions on storage with other products.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

**Engineering measures** : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

## Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

# SikaFix® PU Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 12/21/2016
 100000004232

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove respiratory and skin/eye protection only after vapors

have been cleared from the area.

Remove contaminated clothing and protective equipment

before entering eating areas.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : straw-like

Odor : mild

Odor Threshold : No data available

pH : not determined

Melting point/range / Freezing

ooint

: No data available

Boiling point/boiling range : No data available

Flash point : ca. 86 °C (187 °F)

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

# SikaFix® PU Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 12/21/2016
 100000004232

Vapor pressure : 0.01 hpa (0.01 mmHg)

Relative vapor density : No data available

Density : 1.020 g/ml (23 °C (73 °F) ())

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Molecular weight : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : No data available

No decomposition if stored and applied as directed.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Not classified based on available information.

## Skin corrosion/irritation

Not classified based on available information.

## Serious eye damage/eye irritation

Not classified based on available information.

## Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

# SikaFix® PU Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 12/21/2016
 100000004232

Respiratory sensitization: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

IARC Not applicable

NTP Not applicable

## Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

Not classified based on available information.

## STOT-repeated exposure

Not classified based on available information.

## **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

## Persistence and degradability

No data available

# **Bioaccumulative potential**

No data available

## Mobility in soil

No data available

#### Other adverse effects

## **Product:**

Additional ecological information

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

# SikaFix® PU Part A



 Version
 Revision Date:
 SDS Number:

 1.2
 12/21/2016
 100000004232

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

**Domestic regulation** 

TDG (road/train)

Not dangerous goods

International Regulations

**IATA-DGR** 

Not dangerous goods

IMDG-Code

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

## **SECTION 16. OTHER INFORMATION**

Revision Date : 12/21/2016

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

#### Full text of other abbreviations

ADR Accord européen relatif au transport international des marchandises





Version 1.2	Revision Date: 12/21/2016	SDS Number: 100000004232
	Dangereuses par Route	
CAS	Chemical Abstracts Service	
DNEL	Derived no-effect level	
EC50	Half maximal effective concentra	ation
GHS	Globally Harmonized System	
IATA	International Air Transport Asso	ciation
IMDG	International Maritime Code for I	Dangerous Goods
LD50		t of a material, given all at once, which
	causes the death of 50% (one h	
LC50		ncentrations of the chemical in air that
	kills 50% of the test animals dur	
MARPOL		Prevention of Pollution from Ships, 1973
0.51	as modified by the Protocol of 19	978
OEL	Occupational Exposure Limit	
PBT	Persistent, bioaccumulative and	
PNEC	Predicted no effect concentration	
REACH		of the European Parliament and of the
		oncerning the Registration, Evaluation,
		Chemicals (REACH), establishing a
SVHC	European Chemicals Agency Substances of Very High Conce	arn.
vPvB	Very persistent and very bioacci	
VI VD	very persistent and very bloacet	umulative

CA / Z8

# SikaFix® PU Part B



Version Revision Date: SDS Number: 1.3 12/23/2016 100000004247

#### **SECTION 1. IDENTIFICATION**

Product name : SikaFix® PU Part B

Manufacturer or supplier's details

Sika Canada Inc. Company name

601, avenue Delmar

Pointe-Claire, QC H9R 4A9

Canada www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

## Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

## **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2B

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Specific target organ system-

ic toxicity - single exposure

: Category 3 (Respiratory system)

Specific target organ system-

ic toxicity - repeated expo-

sure (Inhalation)

: Category 2

#### **GHS** label elements

# SikaFix® PU Part B



 Version
 Revision Date:
 SDS Number:

 1.3
 12/23/2016
 100000004247

Hazard pictograms





Signal Word : Danger

Hazard Statements : H315 + H320 Causes skin and eye irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or re-

peated exposure if inhaled.

Precautionary Statements : Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves.

P284 In case of inadequate ventilation wear respiratory protec-

tion.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

DOOD DOOD If alsie is it

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

**Supplemental information** 

# SikaFix® PU Part B



 Version
 Revision Date:
 SDS Number:

 1.3
 12/23/2016
 100000004247

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

## **Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 40 - < 50
Diphenylmethanediisocyanate, isomeres and	9016-87-9	>= 35 - < 45
homologues		
o-(p-isocyanatobenzyl)phenyl isocyanate (MDI)	5873-54-1	>= 20 - < 25

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects sensitizing effects Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Headache

See Section 11 for more detailed information on health effects

and symptoms.

Causes skin and eye irritation.

May cause an allergic skin reaction.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation.

# SikaFix® PU Part B



Version **Revision Date:** SDS Number: 1.3 12/23/2016 100000004247

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

: Collect contaminated fire extinguishing water separately. This Further information

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. Environmental precautions

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms.

# SikaFix® PU Part B



Version Revision Date: SDS Number: 1.3 12/23/2016 100000004247

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Protect from frost.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.005 ppm 0.05 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA BC OEL
		С	0.01 ppm	CA BC OEL
		TWAEV	0.005 ppm	CA QC OEL
			0.051 mg/m3	
		TWA	0.005 ppm	CA ON OEL
		С	0.02 ppm	CA ON OEL
		TWA	0.005 ppm	ACGIH
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0.005 ppm 0.07 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA BC OEL
		С	0.01 ppm	CA BC OEL
o-(p-isocyanatobenzyl)phenyl isocyanate (MDI)	5873-54-1	TWA	0.005 ppm	CA ON OEL
		С	0.02 ppm	CA ON OEL
		TWA	0.005 ppm	CA ON OEL
		С	0.02 ppm	CA ON OEL

## **Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

## Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when han-

# SikaFix® PU Part B



 Version
 Revision Date:
 SDS Number:

 1.3
 12/23/2016
 100000004247

dling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : brown

Odor : mild

Odor Threshold : No data available

pH : not determined

Melting point/range / Freezing

ooint

: No data available

Boiling point/boiling range : No data available

Flash point :  $> 110 \, ^{\circ}\text{C} (230 \, ^{\circ}\text{F})$ 

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

# SikaFix® PU Part B



 Version
 Revision Date:
 SDS Number:

 1.3
 12/23/2016
 10000004247

Relative vapor density : No data available

Density : ca. 1.220 g/ml (23 °C (73 °F) ())

Solubility(ies)

Water solubility : not determined

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Molecular weight : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Harmful if inhaled.

**Product:** 

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

## **Ingredients:**

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

# SikaFix® PU Part B



 Version
 Revision Date:
 SDS Number:

 1.3
 12/23/2016
 100000004247

Test atmosphere: dust/mist Method: Expert judgment

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

## Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes eye irritation.

## Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if in-

haled.

## Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

IARC Not applicable

NTP Not applicable

## Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

May cause respiratory irritation.

## STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

No data available

## Persistence and degradability

No data available

# SikaFix® PU Part B



 Version
 Revision Date:
 SDS Number:

 1.3
 12/23/2016
 100000004247

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

# **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

**Domestic regulation** 

TDG (road/train)

Not dangerous goods

**International Regulations** 

**IATA-DGR** 

Not dangerous goods

**IMDG-Code** 

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **SECTION 15. REGULATORY INFORMATION**

**Canadian lists** 

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

Revision Date : 12/23/2016

## SAFFTY DATA SHFFT

# SikaFix® PU Part B



Version **Revision Date:** SDS Number: 1.3 12/23/2016 100000004247

Prepared by : R & D of Sika Canada Inc.

## Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

#### Full text of other abbreviations

**ADR** Accord européen relatif au transport international des marchandises

Dangereuses par Route

Chemical Abstracts Service CAS **DNEL** Derived no-effect level

EC50 Half maximal effective concentration

**GHS** Globally Harmonized System

IATA International Air Transport Association

**IMDG** International Maritime Code for Dangerous Goods LD50

Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

**MARPOL** International Convention for the Prevention of Pollution from Ships, 1973

as modified by the Protocol of 1978

OEL Occupational Exposure Limit

**PBT** Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

**REACH** Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

**European Chemicals Agency** 

Substances of Very High Concern SVHC

Very persistent and very bioaccumulative vPvB

CA / Z8

# SikaSet® Plug



Version Revision Date: SDS Number: 1.3 12/20/2016 100000004130

#### **SECTION 1. IDENTIFICATION**

Product name : SikaSet® Plug

Manufacturer or supplier's details

Sika Canada Inc. Company name

601, avenue Delmar

Pointe-Claire, QC H9R 4A9

Canada www.sika.ca

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

Health and Safety Services's : ehs@ca.sika.com

e-mail address

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

## Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

## **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ system-

ic toxicity - single exposure

: Category 3 (Respiratory system)

Specific target organ system-

ic toxicity - repeated expo-

sure

: Category 1 (Lungs)

**GHS** label elements

Hazard pictograms







Signal Word : Danger

# SikaSet® Plug



Version **Revision Date:** SDS Number: 1.3 12/20/2016 100000004130

**Hazard Statements** : H315 Causes skin irritation.

> H318 Causes serious eve damage. H335 May cause respiratory irritation. H350i May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure.

: Prevention: **Precautionary Statements** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

P362 + P364 Take off contaminated clothing and wash it before

reuse. Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

# Other hazards

None known.

#### **Supplemental information**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Portland cement	65997-15-1	>= 60 - < 70

# SikaSet® Plug



 Version
 Revision Date:
 SDS Number:

 1.3
 12/20/2016
 100000004130

Quartz (SiO2)	14808-60-7	>= 5 - < 10
calcium oxide	1305-78-8	>= 1 -< 2
Quartz (SiO2) <5µm	14808-60-7	>= 0 - < 1

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects

carcinogenic effects

Cough

Respiratory disorder Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

# SikaSet® Plug



Version **Revision Date:** SDS Number: 1.3 12/20/2016 100000004130

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec: Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. Environmental precautions

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

: Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Prevent unauthorized access.

> Store in original container. Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

# SikaSet® Plug



 Version
 Revision Date:
 SDS Number:

 1.3
 12/20/2016
 100000004130

Le ma Paula	10401	11/-1	0	I p
Ingredients	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
Portland cement	GE007 15 1	exposure) TWA	concentration	CAAROEL
Portiand cement	65997-15-1	TWAEV	10 mg/m3	CA AB OEL CA QC OEL
			5 mg/m3	CA QC OEL
		(respirable		
		dust) TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust)	10 1119/1113	CA QC OEL
		TWA (Res-	1 mg/m3	CA BC OEL
		pirable)	1 1119/1115	OA BO OLL
		TWA (Res-	1 mg/m3	ACGIH
		pirable frac-	1 1119/1115	Addin
		tion)		
Quartz (SiO2)	14808-60-7	TWA (Res-	0.1 mg/m3	CA ON OEL
Quartz (0102)	1 1000 00 7	pirable frac-	0.1 mg/mo	ON ON OLL
		tion)		
		TWA (Res-	0.025 mg/m3	CA AB OEL
		pirable par-	3	
		ticulates)		
		TWAEV	0.1 mg/m3	CA QC OEL
		(respirable		
		dust)		
		TWA (Res-	0.025 mg/m3	CA BC OEL
		pirable)	(Silica)	
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable frac-	(Silica)	
		tion)		
Limestone	1317-65-3	TWA	10 mg/m3	CA AB OEL
		TWA	10 mg/m3	CA BC OEL
		STEL	20 mg/m3	CA BC OEL
		TWAEV (to-	10 mg/m3	CA QC OEL
		tal dust)		
gypsum (containing less than	13397-24-5	TWA	10 mg/m3	CA AB OEL
2% free crystalline silica in the				
respirable fraction)				
		TWA	10 mg/m3	CA BC OEL
		STEL	20 mg/m3	CA BC OEL
		TWAEV	5 mg/m3	CA QC OEL
		(respirable		
		dust)		
		TWAEV (to-	10 mg/m3	CA QC OEL
	<u> </u>	tal dust)	1.2	1000
		TWA (Inhal-	10 mg/m3	ACGIH
	1005 70 0	able fraction)	(Calcium)	04.45.05
calcium oxide	1305-78-8	TWA	2 mg/m3	CA AB OEL
		TWA	2 mg/m3	CA BC OEL
	<u> </u>	TWAEV	2 mg/m3	CA QC OEL
		TWA	2 mg/m3	ACGIH
magnesium oxide	1309-48-4	TWA (Inhal-	10 mg/m3	CA BC OEL
		able fume)	(Magnesium)	
		TWA (Res-	3 mg/m3	CA BC OEL
		pirable dust	(Magnesium)	

# SikaSet® Plug



 Version
 Revision Date:
 SDS Number:

 1.3
 12/20/2016
 10000004130

		and fume)		
		STEL (Res- pirable dust and fume)	10 mg/m3 (Magnesium)	CA BC OEL
		TWA (Fumes)	10 mg/m3	CA AB OEL
		TWAEV (Fumes)	10 mg/m3 (Magnesium)	CA QC OEL
		TWA (Inhal- able fraction)	10 mg/m3	ACGIH
Quartz (SiO2) <5μm	14808-60-7	TWA (Res- pirable frac- tion)	0.1 mg/m3	CA ON OEL
		TWA (Respirable particulates)	0.025 mg/m3	CA AB OEL
		TWAEV (respirable dust)	0.1 mg/m3	CA QC OEL
		TWA (Respirable)	0.025 mg/m3 (Silica)	CA BC OEL
		TWA (Res- pirable frac- tion)	0.025 mg/m3 (Silica)	ACGIH

## **Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

#### Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

# SikaSet® Plug



 Version
 Revision Date:
 SDS Number:

 1.3
 12/20/2016
 100000004130

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Avoid breathing dust.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder

Color : gray

Odor : odorless

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : Not applicable

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

# SikaSet® Plug



 Version
 Revision Date:
 SDS Number:

 1.3
 12/20/2016
 100000004130

Viscosity, dynamic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Molecular weight : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye damage.

## Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

Quartz (SiO2) <5µm 14808-60-7

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

Quartz (SiO2) <5µm 14808-60-7

# SikaSet® Plug



 Version
 Revision Date:
 SDS Number:

 1.3
 12/20/2016
 100000004130

## Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

#### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

## Persistence and degradability

No data available

## Bioaccumulative potential

No data available

## Mobility in soil

No data available

#### Other adverse effects

## **Product:**

Additional ecological infor-

mation

: Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

## **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

## **SECTION 14. TRANSPORT INFORMATION**

**Domestic regulation** 

TDG (road/train)

Not dangerous goods

## International Regulations

# SikaSet® Plug



 Version
 Revision Date:
 SDS Number:

 1.3
 12/20/2016
 100000004130

**IATA-DGR** 

Not dangerous goods **IMDG-Code** 

Not dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **SECTION 15. REGULATORY INFORMATION**

#### **Canadian lists**

No substances are subject to a Significant New Activity Notification.

#### **SECTION 16. OTHER INFORMATION**

Revision Date : 12/20/2016

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

## Full text of other abbreviations

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route Chemical Abstracts Service

CAS Chemical Abstracts Serv DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships, 1973





Version 1.3	Revision Date: 12/20/2016	SDS Number: 10000004130
	as modified by the Protocol of 19	978
OEL	Occupational Exposure Limit	
PBT	Persistent, bioaccumulative and	toxic
PNEC	Predicted no effect concentration	1
REACH	Regulation (EC) No 1907/2006 o	of the European Parliament and of the
		oncerning the Registration, Evaluation,
	Authorisation and Restriction of C	Chemicals (REACH), establishing a
	European Chemicals Agency	
SVHC	Substances of Very High Concer	
vPvB	Very persistent and very bioaccu	ımulative
CA / Z8		